

®

TropiCal





An economy heat pump designed to fit any budget

- Optimum heat output in small footprint
- Large surface and corrosion resistant evaporator
- Vinyl coated fan grill
- Microprocessor controlled automatic defrost allows operation down to the mid to lower 40s
- High performance titanium heat exchanger (Patented ThermoLink heat exchanger in T115 model)



MADE IN USA



BTUs	T55	T75	T115
80/80/80*	50,000	70,000	112,000
80/80/63**	47,500	67,000	106,000
80/50/63**	30,000	46,000	74,000
Coefficient of Performance			
80/80/80*	5.8	5.5	5.7
80/80/63**	5.5	5.3	5.4
80/50/63**	4.0	4.0	4.0
Refrigerant			
	R410A	R410A	R410A
Heat Exchanger			
	Tube in Tube	Tube in Tube	ThermoLink
Electrical			
KW Input	2.5	3.7	5.8
Voltage/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Minimum Circuit Ampacity	19.7	25.8	40
Maximum Fuse Size	30	45	60
Water Flow			
Minimum/Maximum (gpm)	20/45	20/45	30/70
Physical			
Physical Weight (lbs)	230	265	300
Shipping Weight (lbs)	240	275	310
Size (LxWxH)	36"x24"x27"	36"x24"x31"	37"x28"x37"
Decibels (dB)			
	65	65	65

* - ratings outside the scope of the ARI standard 1160 water temp/ambient air/relative humidity

** - rated in accordance with ARI standard 1160 water temp/ambient air/relative humidity

