



DEPENDABILITY and
EFFICIENCY for
pool heating and cooling

Control from a
CONVENIENT
phone app

TropiCal[®]



GET THE MOST OUT OF YOUR POOL HEATING INVESTMENT!

		T170R
Efficiency	kW Output	48.0
	BTU Output	164,000
	C.O.P. Coefficient of Performance	6.7
	kW Input	7.2
Electrical	Heat or Heat & Cool	H & C
	Voltage/Hz/Phase	D
D - 380-415/50/3	Max. Fuse Size	D - 35
	Min. Circuit Ampacity	D - 22.0
Over Temperature Alarm Kit available: part number STK0221 for single phase, STK0222 for three phase. Strongly recommended for all spa applications.		
Refrigerant		R410A
Heat Exchanger		ThermoLink®
Water Flow	Min./Max. (m ³ /h)	6.8/15.9
	Min./Max. (gpm)	30/70
A Heater Bypass Kit is required when flow rates exceed the maximum: part number STK0135		
Physical	Weight (kg)	146
	Weight (lbs)	320
	Length x Width x Height (cm)	89 x 92 x 106
	Length x Width x Height (in)	35" x 36" x 42"
Shipping	Weight (kg)	164
	Weight (lbs)	360
	Length x Width x Height (cm)	97 x 115 x 120
	Length x Width x Height (in)	38" x 45" x 47"
Specifications subject to change		

Smart Microprocessor Control with LCD Display

- High performance patented ThermoLink® titanium heat exchanger
- Lockable control panel can be easily programmed to prevent others from tampering with settings
- Digital control panel with 24 character full-text display provides easy-to-read menu options and unit status
- Ability to connect to most external controllers for heating and cooling mode
- Hybrid functionality can initiate a gas heater when an extra boost of heat is needed
- Impact resistant, rust and fade proof cabinet
- Quieter than conventional heat pumps

Now PoolSync™ Ready

- Adjust the mode to heat, cool or autotemp, and set your temperature through the PoolSync app

*Additional purchase of PoolSync WiFi Controller required



AquaCal®
Producing quality heat pumps since 1981

WWW.
AQUACAL
.COM

MADE IN USA 



AC-1430 11_20 V3