



# WATER SOURCE®

Consistent **GEOTHERMAL**  
heating for your **POOL** or  
**SPA** in any **TEMPERATURE**



PoolSync  
**READY!**

WS03 | WS05 | WS10

# THE WATER SOURCE GEOTHERMAL HEATER TRANSFERS FREE HEAT

from nearby wells, lakes, canals, oceans, or closed loop systems to your pool.

- SMART control panel with 24 character full-text display provides easy-to-read menu options and unit status
- Consistent heating or cooling for your pool or spa in any temperature (Heat and cool standard on WS05 and WS10)
- Attractive marine grade aluminum for strength & durability
- Units with hard copper plumbing available for high pressure installations
- Patented high performance ThermoLink® titanium heat exchanger maximizes flow efficiency

## PoolSync® Technology

- Adjust heating, cooling, and autotemp modes via the PoolSync® app
- Enables remote diagnostics, instant performance updates and quick troubleshooting
- Monitors operation in real-time and ensures reliable performance year-round

\* Additional purchase of PoolSync WiFi Controller required

## UNIT SPECIFICATIONS

SOURCE SIDE TITANIUM				SOURCE SIDE CUPRONICKEL		
				Required for high pressure and cooling tower applications		
	WS03-TT	WS05-TT	WS10-TT	WS03-TC	WS05-TC	WS10-TC
<b>Efficiency</b> 50/70° Source Water Temp (80° Pool Temp)	BTUs	44,000/56,000	75,000/94,000	169,000/213,000	32,000/45,000	67,000/84,000
	C.O.P. (Coefficient of Performance)	5.6/7.2	4.5/5.5	5.0/6.3	4.5/5.8	3.9/4.7
	kW Input	2.3/2.3	4.9/5.0	9.9/9.9	2.0/2.3	5.0/5.2
<b>Electrical</b>  A Voltage - 208-230V/60Hz/1ph B Voltage - 208-230V/60Hz/3ph G Voltage - 460V/60Hz/3ph	Voltage/Hz/Phase	A	A, B & G	B & G	A	A, B & G
	Max. Fuse Size	A - 35	A - 60 B - 50 G - 20	B - 100 G - 50	A - 35	A - 60 B - 50 G - 20
	Min. Circuit Ampacity	A - 20.8	A - 40.1 B - 29.0 G - 13.2	B - 64.1 G - 28.8	A - 20.8	A - 40.1 B - 29.0 G - 13.2
	Over Temperature Alarm Kit required to heat spas over 96°F; Part number STK0221 for single phase, STK0222 for three phase.					
<b>Refrigerant</b>	R410A		R410A	R410A	R410A	R410A
<b>Heat &amp; Cool</b>	H		H & C	H & C	H & C	H & C
<b>Water Flow</b> (gpm)	SOURCE Min./Max.	30/70	30/70	30/70	10/14	10/18
	POOL/SPA Min./Max.	30/70	30/70	30/70	30/70	30/70
<b>Physical</b>	Weight (lbs)	290	300	745	300	320
	Length x Width x Height (in)	32" x 37" x 32"	32" x 37" x 32"	35" x 61" x 40"	32" x 37" x 32"	32" x 37" x 32"
<b>Shipping</b>	Weight (lbs)	320	330	805	330	350
	Length x Width x Height (in)	39" x 46" x 51"	39" x 46" x 51"	45" x 69" x 48"	39" x 46" x 51"	39" x 46" x 51"
35" x 69" x 48"						

Specifications subject to change. California residents visit aquacal.com for Proposition 65 information.



A portion of every heat pump sold will  
be donated to Every Child a Swimmer



MADE IN USA